



# Nylon Web Slings

Stock No.	Width (in.)	Ply	Vert.	Choker	Basket Hitch			Nominal Eye Length L (in.)	Nominal Eye Width W (in.)	
					60°	45°	30°			
*1-901	1	1	1,600	1,300	3,200	2,800	2,300	1,600	9	1
2-901	1	2	3,200	2,600	6,400	5,500	4,500	3,200	9	1
3-901	1	3	4,100	3,300	8,200	7,100	5,800	4,100	12	1
4-901	1	4	5,500	4,400	11,000	9,500	7,800	5,500	12	1
1-902	2	1	3,200	2,600	6,400	5,500	4,500	3,200	9	2
2-902	2	2	6,400	5,100	12,800	11,100	9,000	6,400	9	2
3-902	2	3	8,200	6,600	16,500	14,300	11,600	8,200	12	2
4-902	2	4	11,000	8,800	22,000	19,000	15,500	11,000	12	2
1-903	3	1	4,800	3,800	9,600	8,300	6,800	4,800	12	1-1/2
2-903	3	2	8,900	7,100	17,800	15,400	12,600	8,900	12	1-1/2
3-903	3	3	12,300	9,900	24,700	21,400	17,500	12,300	15	1-1/2
4-903	3	4	16,500	13,200	32,900	28,500	23,300	16,500	15	1-1/2
1-904	4	1	6,400	5,100	12,800	11,100	9,000	6,400	12	2
2-904	4	2	11,500	9,200	23,000	20,000	16,300	11,500	12	2
3-904	4	3	15,300	12,200	30,600	26,500	21,600	15,300	15	2
4-904	4	4	20,400	16,300	40,800	35,300	28,800	20,400	15	2
1-906	6	1	9,600	7,700	19,200	16,600	13,600	9,600	12	2
2-906	6	2	16,300	13,100	32,600	28,300	23,100	16,300	15	2
3-906	6	3	22,900	18,300	45,900	39,700	32,400	22,900	18	3
4-906	6	4	30,600	24,500	61,200	53,000	43,200	30,600	18	3
1-908	8	1	12,800	10,200	25,600	22,200	18,100	12,800	18	3
2-908	8	2	20,500	16,400	41,000	35,500	29,000	20,500	18	3
3-908	8	3	30,700	24,600	61,400	53,200	43,400	30,700	24	4
4-908	8	4	41,000	32,800	81,900	70,900	57,900	41,000	24	4
1-910	10	1	16,000	12,800	32,000	27,700	22,600	16,000	18	3-1/2
2-910	10	2	24,000	19,200	48,000	41,600	33,900	24,000	18	3-1/2
3-910	10	3	36,000	28,800	72,000	62,300	50,900	36,000	24	5
4-910	10	4	48,000	38,400	96,000	83,100	67,900	48,000	24	5
1-912	12	1	19,200	15,400	38,400	33,200	27,100	19,200	24	4
2-912	12	2	26,900	21,500	53,700	46,500	38,000	26,900	24	4
3-912	12	3	40,300	32,200	80,600	69,800	57,000	40,300	24	6
4-912	12	4	53,700	43,000	107,400	93,000	76,000	53,700	24	6



Eye & Eye - Flat  
Eye & Eye - Twist

\*Insert EEF prefix to indicate Type 3 and EET prefix to indicate Type 4.  
**Warning:** Horizontal sling angles less than 30° shall not be used.



## Endless

These are nylon or polyester web slings designed for use in vertical, choker and basket hitches. Legs may be spaced for load stability. Hook points can be tapered to fit hoist hooks and are reinforced upon request.

Stock No.	Width (in.)	Ply	Vert.	Choker	Basket Hitch			Taper		
					60°	45°	30°	Width W (in.)	Length L (in.)	
EN-1-901	1	1	3,200	2,600	6,400	5,500	4,500	3,200	—	—
EN-2-901	1	2	6,400	5,100	12,800	11,100	9,000	6,400	—	—
EN-3-901	1	3	8,200	6,600	16,500	14,300	11,600	8,200	—	—
EN-4-901	1	4	11,000	8,800	22,000	19,000	15,500	11,000	—	—
EN-1-902	2	1	6,400	5,100	12,800	11,100	9,000	6,400	1	9
EN-2-902	2	2	12,800	10,200	25,600	22,200	18,100	12,800	1	9
EN-3-902	2	3	16,500	13,200	32,900	28,500	23,300	16,500	*	*
EN-4-902	2	4	22,000	17,600	43,900	38,000	31,000	22,000	—	—
EN-1-903	3	1	9,600	7,700	19,200	16,600	13,600	9,600	1-1/2	12
EN-2-903	3	2	17,800	14,200	35,500	30,800	25,100	17,800	1-1/2	12
EN-3-903	3	3	24,700	19,800	49,400	42,800	34,900	24,700	*	*
EN-4-903	3	4	32,900	26,300	65,900	57,700	46,600	32,900	—	—
EN-1-904	4	1	12,800	10,200	25,600	22,200	18,100	12,800	2	12
EN-2-904	4	2	23,000	18,400	46,100	39,900	32,600	23,000	2	12
EN-3-904	4	3	30,600	24,500	61,200	53,000	43,200	30,600	*	*
EN-4-904	4	4	40,800	32,600	81,500	70,600	57,000	40,800	—	—
EN-1-906	6	1	19,200	15,400	38,400	33,200	27,100	19,200	2	15
EN-2-906	6	2	32,600	26,100	65,300	56,500	46,200	32,600	3	15
EN-3-906	6	3	45,900	36,700	91,700	79,400	64,900	45,900	*	*
EN-4-906	6	4	61,200	48,900	122,300	105,900	86,500	61,200	—	—
EN-1-908	8	1	25,600	20,500	51,200	44,300	36,200	25,600	3	18
EN-2-908	8	2	41,000	32,800	81,900	70,900	57,900	41,000	4	18
EN-3-908	8	3	61,400	49,100	122,900	106,400	86,900	61,400	*	*
EN-4-908	8	4	81,900	65,500	163,800	141,900	115,800	81,900	—	—
EN-1-910	10	1	32,000	25,600	64,000	55,400	45,200	32,000	3-1/2	18
EN-2-910	10	2	48,000	38,400	96,000	83,100	67,900	48,000	5	18
EN-3-910	10	3	72,000	57,600	143,900	124,700	101,800	72,000	*	*
EN-4-910	10	4	96,000	76,800	191,900	166,200	135,700	96,000	—	—
EN-1-912	12	1	38,400	30,700	76,800	66,500	54,300	38,400	4	18
EN-2-912	12	2	53,700	43,000	107,400	93,000	76,000	53,700	6	18
EN-3-912	12	3	80,600	64,500	161,200	139,600	114,000	80,600	*	*
EN-4-912	12	4	107,400	86,000	214,900	186,100	151,900	107,400	—	—

Please specify when sling is to be tapered at hook contact area.

\*Three-ply slings are tapered by special request only.

**Warning:** Horizontal sling angles less than 30° shall not be used.