















**PACIFIC NORTHWEST  
GULF COAST • CALIFORNIA  
RENTALS • SALES • PARTS  
(800) 227-7920  
Info@rasmussenco.com  
www.RasmussenCo.com**



Images shown are representative samples of equipment models only.

35,001 – 75,000 DIESEL MECHANICAL WINCHES	MANF.	MODEL # DRUMS	WEIGHT	CONTROL TYPE	TRANSMISSION TYPE	SPEC SHEET
	Clyde	Frame 7 / 1 Drum	9,500 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 2540' of 1", 3310' of 7/8", 4520' of 3/4"						
APPROX BARE DRUM PULL & SPEED 40,000 lbs @ 20 FPM			APPROX DIMENSIONS L=116"xW=90"xH=84"			
	Clyde	Frame 7 / 2 Drum	12,700 lbs	Manually Controlled	Torque Converter	
DRUM CAPACITY 2549' of 1", 3310' of 7/8", 4520' of 3/4"						
APPROX BARE DRUM PULL & SPEED 40,000 lbs @ 20 FPM			APPROX DIMENSIONS L=151"xW=90"xH=75"			
	Clyde	Frame 7 / 2 Drum	12,700 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 2549' of 1", 3310' of 7/8", 4520' of 3/4"						
APPROX BARE DRUM PULL & SPEED 40,000 lbs @ 20 FPM			APPROX DIMENSIONS L=151"xW=90"xH=75"			
	Amclyde	Frame 7 / 2 Drum	15,000 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 2549' of 1", 3310' of 7/8", 4520' of 3/4"						
APPROX BARE DRUM PULL & SPEED 40,000 lbs @ 20 FPM			APPROX DIMENSIONS L=168"xW=92"xH=111"			

35,001 - 75,000 DIESEL MECHANICAL WINCHES	MANF.	MODEL # DRUMS	WEIGHT	CONTROL TYPE	TRANSMISSION TYPE	SPEC SHEET
	Clyde	Frame 7 / 2 Drum	12,700 lbs	Air Controlled	Transmission	
DRUM CAPACITY 2540' of 1", 3310' of 7/8", 4520' of 3/4"						
APPROX BARE DRUM PULL & SPEED 40,000 lbs @ 20 FPM			APPROX DIMENSIONS L=151"xW=90"xH=75"			
	Clyde	Frame 7 / 3 Drum	17,950 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 2549' of 1", 3310' of 7/8", 4520' of 3/4"						
APPROX BARE DRUM PULL & SPEED 40,000 lbs @ 20 FPM			APPROX DIMENSIONS L=190"xW=90"xH=75"			
	Clyde	Frame 10 / 2 Drum	37,000 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 4000' of 1-1/4", 2930' of 1-1/2"						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 10			APPROX DIMENSIONS L=192"xW=114"xH=100"			
	Clyde	Frame 8 / 2 Drum	18,200 lbs	Manually Controlled	Torque Converter	
DRUM CAPACITY 2180' of 1-1/4", 2690' of 1-1/8", 3400' of 1"						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 20 FPM			APPROX DIMENSIONS L=171"xW=106"xH=86"			
	Clyde	Frame 8 / 2 Drum	18,200 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 2180' of 1-1/4", 2690' of 1-1/8", 3400' of 1"						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 20 FPM			APPROX DIMENSIONS L=171"xW=106"xH=86"			
	Clyde	Frame 8 / 2 Drum	18,200 lbs	Air Controlled	Hydraulic Motor	
DRUM CAPACITY 2180' of 1-1/4", 2690' of 1-1/8", 3400' of 1" w/ fleeting sheaves						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 20 FPM			APPROX DIMENSIONS L=171"xW=106"xH=86"			

35,001 - 75,000 DIESEL MECHANICAL WINCHES	MANF.	MODEL # DRUMS	WEIGHT	CONTROL TYPE	TRANSMISSION TYPE	SPEC SHEET
	Clyde	Frame 8 / 3 Drum	26,225 lbs	Manually Controlled	Torque Converter	
DRUM CAPACITY 2180' of 1-1/4", 2690' of 1-1/8", 3400' of 1"						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 20 FPM			APPROX DIMENSIONS L=196"xW=106"xH=86"			
	Clyde	Frame 8 / 3 Drum	26,225 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 2180' of 1-1/4", 2690' of 1-1/8", 3400' of 1"						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 20 FPM			APPROX DIMENSIONS L=196"xW=106"xH=86"			
	Skagit	G-95 / 2 Drum	18,000 lbs	Manually Controlled	Transmission	
DRUM CAPACITY 2200' of 1-1/8", 2800' of 1", 3600' of 7/8", 4900' of 3/4"						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 35 FPM			APPROX DIMENSIONS L=123"xW=98"xH=77"			
	Skagit	G-95 / 2 Drum	20,000 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 2200' of 1-1/8", 2800' of 1", 3600' of 7/8", 4900' of 3/4"						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 35 FPM			APPROX DIMENSIONS L=123"xW=98"xH=77"			
	Amclyde	Model Frame 8 / 2 Drum	22,200 lbs	Air Controlled	Hydraulic Motor	
DRUM CAPACITY 2180' of 1-1/4", 2690' of 1 1/8" w/Fleeting sheaves						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 20 FPM			APPROX DIMENSIONS L=180"xW=91"xH=103"			
	Rasmussen	RAS4565 / 3 Drum	15,000 lbs	Air Controlled	Transmission	
DRUM CAPACITY 1450' of 1", 1879' of 7/8", 2550' of 3/4", 3670' of 5/8", 5750' of 1/2"						
APPROX BARE DRUM PULL & SPEED 50,000 lbs @ 35 FPM			APPROX DIMENSIONS L=156"xW=72"xH=96"			

35,001 - 75,000 DIESEL MECHANICAL WINCHES	MANF.	MODEL # DRUMS	WEIGHT	CONTROL TYPE	TRANSMISSION TYPE	SPEC SHEET
	Skagit	G-120 / 2 Drum	22,000 lbs	Manually Controlled	Transmission	
DRUM CAPACITY 1790' of 1-3/8", 2170' of 1-1/4", 2680' of 1-1/8"						
APPROX BARE DRUM PULL & SPEED 55,000 lbs @ 50 FPM			APPROX DIMENSIONS L=150"xW=103"xH=78"			
	Skagit	G-120 / 2 Drum	26,000 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 1790' of 1-3/8", 2170' of 1-1/4", 2680' of 1-1/8"						
APPROX BARE DRUM PULL & SPEED 55,000 lbs @ 50 FPM			APPROX DIMENSIONS L=150"xW=103"xH=78"			
	Skagit	G-120 / 3 Drum	28,000 lbs	Manually Controlled	Transmission	
DRUM CAPACITY 1790' of 1-3/8", 2170' of 1-1/4", 2680' of 1-1/8"						
APPROX BARE DRUM PULL & SPEED 55,000 lbs @ 50 FPM			APPROX DIMENSIONS L=185"xW=103"xH=64"			
	Skagit	G-120 / 3 Drum	30,000 lbs	Air Controlled	Torque Converter	
DRUM CAPACITY 1790' of 1-3/8", 2170' of 1-1/4", 2680' of 1-1/8"						
APPROX BARE DRUM PULL & SPEED 55,000 lbs @ 50 FPM			APPROX DIMENSIONS L=185"xW=103"xH=64"			